U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

IMPORTANT: Follow the instructions on pages 1-9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

SECTION A - PROPERTY INFORMATION FOR INSURANCE COMPANY USE Building Owner's Name Policy Number: R, & JAMIED, WEWER Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or PO. Route and Box No. Company NAIC Number: CityMARGATE 08402 A3. Property Description (Lot and Block Numbers, Tax Parcel Number, Legal Description, etc.) BLOCK 318 A4. Building Use (e.g., Residential, Non-Residential, Addition, Accessory, etc.) 125106 A5. Latitude/Longitude: Lat. 29.32743° Long. 74.50958° RESIDENTIAL Horizontal Datum: ☐ NAD 1927 M NAD 1983 A6. Attach at least 2 photographs of the building if the Certificate is being used to obtain flood insurance. A7. Building Diagram Number A8. For a building with a crawlspace or enclosure(s): A9. For a building with an attached garage: a) Square footage of crawlspace or enclosure(s) sa ft a) Square footage of attached garage sa ft b) No. of permanent flood openings in the crawlspace or b) Number of permanent flood openings in the attached garage enclosure(s) within 1.0 foot above adjacent grade within 1.0 foot above adjacent grade c) Total net area of flood openings in A8.b Total net area of flood openings in A9.b d) Engineered flood openings? ΠNo d) Engineered flood openings? SECTION B - FLOOD INSURANCE RATE MAP (FIRM) INFORMATION B1. NFIP Community Name & Community Number CITY OF MARGATE CITY 345304 B2. County Name B3. State ANTIC ATL B4. Map/Panel Number B5. Suffix B6. FIRM Index Date B7. FIRM Panel Effective/ B8. Flood Zone(s) B9. Base Flood Elevation(s) (Zone Revised Date AO, use base flood depth) 345304 0001 18/83 10/ 10/18/83 A8 10,0 B10. Indicate the source of the Base Flood Elevation (BFE) data or base flood depth entered in Item B9: S FIRM ☐ Community Determined Other/Source: B11. Indicate elevation datum used for BFE in Item B9: **™** NGVD 1929 ■ NAVD 1988 Other/Source: B12.Is the building located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA)? _/____ CBRS ☐ OPA SECTION C - BUILDING ELEVATION INFORMATION (SURVEY REQUIRED) 14-230 Building elevations are based on: ☐ Construction Drawings* ☐ Building Under Construction* Finished Const *A new Elevation Certificate will be required when construction of the building is complete. C2. Elevations - Zones A1-A30, AE, AH, A (with BFE), VE, V1-V30, V (with BFE), AR, AR/A, AR/AE, AR/A1-A30, AR/AH, AR/AO. Con C2.a-h below according to the building diagram specified in Item A7. In Puerto Rico only, enter meters. RM 4 NGVD 1929 Benchmark Utilized: _ Vertical Datum: _ Indicate elevation datum used for the elevations in items a) through h) below. X NGVD 1929 NAVD 1988 Other/Source; Datum used for building elevations must be the same as that used for the BFE. Check the measurement used. a) Top of bottom floor (including basement, crawlspace, or enclosure floor) feet meters 12 b) Top of the next higher floor feet meters NIA c) Bottom of the lowest horizontal structural member (V Zones only) feet meters NIA d) Attached garage (top of slab) feet meters 9 12 e) Lowest elevation of machinery or equipment servicing the building ☑ feet meters (Describe type of equipment and location in Comments) f) Lowest adjacent (finished) grade next to building (LAG) 7 feet □ meters 9 g) Highest adjacent (finished) grade next to building (HAG) feet meters h) Lowest adjacent grade at lowest elevation of deck or stairs, including feet □ meters structural support SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION This certification is to be signed and sealed by a land surveyor, engineer, or architect authorized by law to certify elevation information. I certify that the information on this Certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001, Check here if comments are provided on back of form. Were latitude and longitude in Section A provided by a ☐ Check here if attachments. licensed land surveyor? Yes Certifier's Name License Number HOWARD A GS 3354 SEAL Company Name HERE SCHAEFFER NASSAR SCHEIDEGG, CE PROFE City Code 9/16/2015 NTILLON BOULEVARE MAYS 08330 Signature Date Telephone

(609) 625-7400

LEVATION CERTIFICATE, pag	ge 2				<u> </u>
IMPORTANT: In these spaces, copy	the corresponding information from Section	on A.			INSURANCE COMPANY USE
Building Street Address (including April 106 M. QUINCY	ot., Unit, Suite, and/or Bldg. No.) or P.O. Rou	ite and Box N	0.		y Number:
MARGATE	State V	ZIP Code 0840			pany NAIC Number:
SECTIO	ON D - SURVEYOR, ENGINEER, OR A	RCHITECT	CERTIFICAT	ION (CONTI	NUED)
opy both sides of this Elevation Ce	rtificate for (1) community official, (2) insura	ance agent/c	ompany, and (3)	building own	er.
	CRAWL SPACE DOOR SYSTEM I MODEL 1632CS RATED FURNACE UNIT. THE A.C	07 03	5 50 IN	EACH.	
ignature	lac		9/16/2015		
SECTION E - BUILDING EI	LEVATION INFORMATION (SURVEY	NOT REQUII	RED) FOR ZO	NE AO ANI	ZONE A (WITHOUT BFE)
or Items F1_F4 use natural grade.	omplete Items E1–E5. If the Certificate is ir if available. Check the measurement used	. In Puerto Ric	to only, enter m	eters.	
grade (HAG) and the lowest adja	r the following and check the appropriate bordent grade (LAG).				☐ above or ☐ below the HAG.
b) Top of bottom floor (including	basement, crawlspace, or enclosure) is		leet	meters	above or below the LAG.
2. For Building Diagrams 6–9 with	permanent flood openings provided in Secti	on A Items 8	and/or 9 (see)	pages 8–9 of meters	above or below the HAG.
	C2.b in the diagrams) of the building is				above or below the HAG.
3. Attached garage (top of slab) is	-		71	A STATE OF THE PARTY OF THE PAR	above or below the HAG.
5 Zone AO only: If no flood death	d/or equipment servicing the building isnumber is available, is the top of the bottor] Unknown. The local official must certify the	n floor elevate	ed in accordanc		
SECTI	ON F - PROPERTY OWNER (OR OW	NER'S REP	RESENTATIV	E) CERTIFIC	CATION 14-230
The property owner or owner's authorical authorical AO must sign here. The stater	orized representative who completes Section ments in Sections A, B, and E are correct to	ons A. B. and	E for Zone A (wi	thout a FEMA	rissued or community-issued BFE)
Property Owner or Owner's Authorize	ed Representative's Name				
Address		City		State	ZIP Code
Signature		Date		Teleph	one
Comments					
Commence					
					Check here if attachments
	SECTION G - COMMUNITY				
G of this Elevation Certificate. Comp	by law or ordinance to administer the communities the applicable item(s) and sign below. C	meck the mea	Sulement useu	III ILCINS GO	310. III I doi to 11100 0119,
who is authorized by law t	n C was taken from other documentation to co certify elevation information. (Indicate the leted Section E for a building located in Zor	ie source and	date of the cit	.vation data	il tile sellinistic
G2. A community official comp	(Items G4–G9) is provided for community	floodplain ma	nagement purp	oses.	
G4. Permit Number	G5. Date Permit Issued				mpliance/Occupancy Issued
G7. This permit has been issued	for: New Construction Substan	ntial Improvem	nent		
G8 Flevation of as-built lowest fic			feet	meters	Datum
G9. BFE or (in Zone AO) depth of			feet	meters	Datum
G10. Community's design flood ele			leet	∐ meters	Datum
Local Official's Name JIM GALAN'	TIÑO	Title			
Community Name CITY OF MAR	GATE	Telephor	ne 609-822-197	4	
Signature //C//		Date	9/15/15		
Comments					
					☐ Check here if attachment

Certification of Engineered Flood Openings

In accordance with the Code of Federal Regulations for the National Flood Insurance Program

I hereby certify that the Crawl Space Door Systems flood vents 816CS, 1220CS, 1232CS, 1616CS, 1624CS, 1632CS, 2032CS, 2424CS, and 2436CS are designed are designed in accordance with the requirements of the Code of Federal Regulations for the National Flood Insurance Program (NFIP) to provide automatic equalization of hydrostatic flood forces by allowing for the entry and exit of floodwaters, when properly installed and sized as set forth below. Vent opening measurements were measured and certified by Mr. Christopher Mark Loney, Virginia P.E. NO. 029000. Detailed calculations were prepared as outlined in "Review of certification of Engineered Flood Openings," prepared by Dr. Georg Reichard, Associate Professor of Building Construction, Virginia Tech (available upon request from Crawl Space Door Systems, Inc. billy@crawlspacedoors.com)

Design Characteristics

Section 2.6.2.2 of ASCE/SEI 24-05 provides an equation to determine the required net area of engineered openings (A_o) for a given enclosed area (A_e). This equation is based on the hydraulic formula for the flow rate across sharp edged orifices. I have utilized this equation to calculate 1) the restricted flow rate through the main frame opening in case the louver is blown out during a flood event; 2) the flow rate through the individual openings between louver blades; and 3) the flow rate through projected openings between louver blades following hydraulic short-tube theory. The maximum total enclosed area (A_e) that can be serviced by a single vent has then been determined by utilizing the lowest flow rate of the three assessed scenarios for each vent and is listed in Table 1. These values are based on the following assumptions:

- In absence of reliable data, the rates of rise and fall have been assumed at a minimum rate of 5 feet/hour;
- The (maximum) difference between the exterior and interior floodwater levels shall not exceed 1 foot during base flood conditions;
- A factor of safety of 5 has been assumed, which is consistent with design practices related to protection of life and property;
- The net area of openings (A_o) as provided by the manufacturer.

 * }	*) Model	11 X VV	Αď	Aو
		[in]	[in²]	[ft²]
	816CS	8 x 16	105	205
	1220CS	12 x 20	235	500
	1232CS	12 x 32	305	645
	1616CS	16 x 16	180	395
	1624CS	16 x 24	310	670
O	1632CS	16 x 32	405	835
	2032CS	20 x 32	630	1240
口	2424CS	24 x 24	570	1230
	2436CS	24 x 36	850	1765

HVW

Table 1 Maximum total <u>enclosed</u> <u>area</u> (A_e) that can be serviced by each individual model based on the given <u>net area</u> of engineered openings (A_o)

Installation Requirements and Limitations

This certification will be voided if the following installation requirements and limitations are not enforced:

- There shall be a minimum of two openings on different sides of each enclosed area subject to flooding;
- The bottom of all openings shall be no higher than one foot given net are above the higher of the interior or exterior grade that is immediately under each opening;
- No temporary (e.g. during cold weather) or permanent solid cover may be placed into or over the flood vent that would block the automatic entry or exit of floodwaters at any time;
- Where data or analyses indicate more rapid rates of rise and fall, the required number of openings shall be increased to account
 for those different conditions. The number or size of the openings may be decreased if data or analyses indicate rates of rise
 and fall are less than 5 feet per hour.

certifying Design Professional		
Name WILLIAM S. SWIDERSKI, P.E.	Title ENGINEER	
Company SWIDERSKI ASSSOCIATES		
Address 599 SHORE ROAD SOMERS POINT, NJ		
License PROFESSIONAL ENGINEER	License No. 24GE02048200	
Signature: Mm () ()	Date:	
dentification of the Building and Installed Flo	ood Vents (Ry Others)	
he flood vent models marked in Table 1*) are being installed	at the following building:	
		_

5pring 2012

Building Address