U.S. DEPARTMENT OF HOMELAND SECURITY Federal Emergency Management Agency National Flood Insurance Program

ELEVATION CERTIFICATE

OMB No. 1660-0008 Expires March 31, 2012

Important: Read the instructions on pages 1-9.

Building Owner's Na	me	SECTI	ON A - PROPERTY INFORM	MATION	For Insurance Company Use:
- 100	A 1 1 1111	10	dg No) or P O Route and Box	and the state of t	Policy Number
3 S. CLERI	ess (including Apt., L MONT AVENU	Init, Suite, and/or Bl	dg. No.) or P.O. Route and Box I	No.	Company NAIC Number
MARCATE		n car	State		ZIP Code
A. Property Description	Lot and Block Num	horo Toy Bareel Nu	mber, Legal Description, etc.)		08402
44. Building Lies (BLOCK 103,0	Ders, Tax Parcer Nu	mber, Legal Description, etc.)		
			cessory, etc.)	TIAL	18 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
A7. Building Di	graphs of the buildi	ing if the Cartificate	is being used to obtain flood inst	Horizontal Darance.	atum: NAD 1927 NAD 1983
A8. For a building with a cr a) Square footage of (awlspace or enclose				
D) No. of permanent a	space or enclo	osure(s)		building with an attac quare footage of attac	
enclosuro/ol	openings in the	e crawienace or	b) N	o. of permanent flood	openings in the attached garage
				thin 1.0 foot above actal net area of flood	
d) Engineered flood op	enings? X Yes	. No □		ngineered flood open	
1 NEIR C	SECTIO	ON B - FLOOD IN	SURANCE RATE MAP (FIR	M) INFORMATION	offer of the property of
1. NFIP Community Name 8	Community Num	nber B	2. County Name	A professional and the second	B3. State
4. Map/Panel Number	34530	94	ATLANTIC		NJ
15 201	B5. Suffix	B6. FIRM Index	B7. FIRM Panel	B8. Flood	B9. Base Flood Elevation(s) (Zone
15304 0001	c	Date	Effective/Revised Date	Zone(s)	AO, use base flood depth)
Indicate the source of the	Base Flood Flow	rotion (REE) data or	base flood depth entered in Item	<u> </u>	10.0
☐ FIS Profile	RM C-	alion (BFE) data of	base flood depth entered in Iter	n B9.	* 178 PRO 8 1 1 2
"Idicate elevation datum.	- 174	Timilarity Botominic	d Guici (Describe)	5 72 352 1	
ne building located in a	Coastal B	tem B9: 🔼 NGVD	1929 NAVD 1988 (CBRS) area or Otherwise Prote	Other (Describe)	
signation Date	- Barrier	Resources System	(CBRS) area or Otherwise Prote	ected Area (OPA)?	Yes No
			CBRS _ OPA		
	CEOTIE				
uilding olevet	SECTION (: - BUILDING EL	EVATION INFORMATION (SURVEY REQUIR	ED) 11-204
Building elevations are base	don: Do	Anna Carlo Barrer Company			
loveticate	Will be Foguired	nstruction Drawings	Building Under Co	onstruction*	Finished Construction
new Elevation Certificate elevations – Zones A1-A30,	AF AH A (when construction	or the building is complete.		
building to the building	og diagram ene	BFE), VE, V1-V30	, V (with BFE), AR, AR/A, AR/A	E, AR/A1-A30, AR/AH	I, AR/AO. Complete Items C2.a-h
enchmark Utilized	M	cilled in item A7. C	, V (with BFE), AR, AR/A, AR/AB Jse the same datum as the BFE.	11600	1000
nversion/Comments	The way be a series	less the colors of the color of	Vertical Datur	$n = N_i G_i V_i D_i$	time to the state of the state
	Part (Train and in	er er er er er er	the second second second second second	Oh Lub and the	A CONTRACTOR OF THE CONTRACTOR
Top of bottom floor (inclu-				Check the measurem	
Top of the next higher flo Bottom of the lowest hori-	oing basement	t, crawlspace, or en	closure floor) 8 3	feet mete	ers (Puerto Rico only)
buttom of the lowest have			1114	H feet H mete	rs (Puerto Rico only)
Attached garage (top of s	Contal structura	al member (V Zone	s only) HA	feet mete	rs (Puerto Rico only)
Lowest elevation of			NIA		rs (Puerto Rico only)
Lowest elevation of mach (Describe type of equipme	nery or equipr	ment servicing the l	ouilding	✓ feet mete	rs (Puerto Rico only)
Lowest adjacent /finish- 1	- a locatio	ii iii Collillelits)			
Highest adjacent (finish -	arade next to	building (LAG)			rs (Puerto Rico only)
owest adjacent grade at I	Owest alarmi	building (HAG)	including 7 9		rs (Puerto Rico only)
Lowest adjacent grade at a structural support	- west elevation	on of deck or stairs	, including	feet mete	rs (Puerto Rico only)
fication is to be size a	SECTION	- SURVEYOR,	ENGINEER, OR ARCHITEC	T CERTIFICATION	v
on. I certify that the inform	sealed by a	land suntainer and	incor or orabita at authorized by	laur to postific aloustin	n
in that any false stateme	nt may be	Certificate represer	nts my best efforts to interpret th imprisonment under 18 U.S. Co	e data available.	
here if comments are pro	Dvid -	instrable by fine or			(N)
	viu ed on bac	K OI IOIIII.	ere latitude and longitude in Sec	tion A provided by a	135/1
Name	*	lic	ensed land surveyor? XYes	i ∐ No	15000
JARD A. TRE	LN SUE		License Number		- GO 10010
565510.111 · · ·	NDUE	mpany Name	G5 3354	1	100
CANTAL LAND	54RVEYO	npany Name 2 SCHAEPS	ER NASSAL SCHEIDEGG	CE LLC	10 21
ANTILLON BL	City	/	State	ZIP Code	
101	m	AYS LANDI	76 A) J Telephone	08330	
181-31, Mar 09		Date /	Lelennone		
01-01 040000	9-1-41 11 1	2/20/20		7400	
91, War 09		2/20/20	reverse side for continuation	with a second second	Replaces all previous editions

IMPORTANT: In these spaces, copy the corresponding information from Section A.	For Insurance Company Use:
Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. る S. CLられのカナ AVENUE	
City State ZIP Cod	
SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION	and the second of the second o
Copy both sides of this Elevation Certificate for (1) community official, (2) insurance agent/company, and (3) build	ling owner.
Comments 17EM ABB-2 CRAWL SPACE DOOR SYSTEMS. MODEL D 1632 R	
5 LOUVRED VENTS. ITEM CZE IS THE FURNACE.	
Signature Date 2/28/2012	Check here if attachments
SECTION E - BUILDING ELEVATION INFORMATION (SURVEY NOT REQUIRED) FOR ZONE	
For Zones AO and A (without BFE), complete Items E1-E5. If the Certificate is intended to support a LOMA or LO and C. For Items E1-E4, use natural grade, if available. Check the measurement used. In Puerto Rico only, ent E1. Provide elevation information for the following and check the appropriate boxes to show whether the elevation grade (HAG) and the lowest adjacent grade (LAG). a) Top of bottom floor (including basement, crawlspace, or enclosure) is feetmeters b) Top of bottom floor (including basement, crawlspace, or enclosure) is feetmeters b) Top of bottom floor (including basement, crawlspace, or enclosure) is feetmeters cleavation C2.b in the diagrams) of the building is feetmeters above or to to feetmeters above or to feetmeters above or below the HAG. E3. Attached garage (top of slab) is feetmeters above or below the HAG. E4. Top of platform of machinery and/or equipment servicing the building is feetmeters feet meters above or below the HAG. E5. Zone AO only: If no flood depth number is available, is the top of the bottom floor elevated in accordance wordinance? Yes No Unknown. The local official must certify, this information in Section G.	OMR-F request, complete Sections A, B, ser meters. Ion is above or below the highest adjacent below the HAG. above or below the HAG. above or below the LAG. as 8-9 of Instructions), the next higher floor below the HAG. above or below the HAG. with the community's floodplain management
SECTION F - PROPERTY OWNER (OR OWNER'S REPRESENTATIVE) C	
The property owner or owner's authorized representative who completes Sections A, B, and E for Zone A (without or Zone AO must sign here. The statements in Sections A, B, and E are correct to the best of my knowledge. Property Owner's Owner's Authorized Representative's Name	t a FEMA-issued or community-issued BFE)
	tate ZIP Code
Address	
Signature Date T	elephone
Comments	
the region of the second of th	Check here if attachments
SECTION G - COMMUNITY INFORMATION (OPTIONAL)	
The local official who is authorized by law or ordinance to administer the community's floodplain management ordinand G of this Elevation Certificate. Complete the applicable item(s) and sign below. Check the measurement used The information in Section C was taken from other documentation that has been signed and sealed by a is authorized by law to certify elevation information. (Indicate the source and date of the elevation data in A community official completed Section E for a building located in Zone A (without a FEMA-issued or cor The following information (Items G4-G9) is provided for community floodplain management purposes.	licensed surveyor, engineer, or architect who he the Comments area below.)
	of Compliance/Occupancy Issued
G7. This permit has been issued for: New Construction Substantial Improvement G8. Elevation of as-built lowest floor (including basement) of the building feet feet feet feet feet feet feet fee	eters (PR) Datumeters (PR) Datumeters (PR) Datumeters (PR)
Local Official's Name James Galantino Title Const	ruction Official
Community Name Margete City Telephone 609-8	22-1974
Signature 2/E3/16	
Comments	
	Check here if attachments

Certification of Engineered Flood Openings

In accordance with the Code of Federal Regulations for the National Flood Insurance Program

I hereby certify that the Crawl Space Door Systems flood vents 816CS, 1220CS, 1232CS, 1616CS, 1624CS, 1632CS, 2032CS, 2424CS, and 2436CS are designed are designed in accordance with the requirements of the Code of Federal Regulations for the National Flood Insurance Program (NFIP) to provide automatic equalization of hydrostatic flood forces by allowing for the entry and exit of floodwaters, when properly installed and sized as set forth below. Vent opening measurements were measured and certified by Mr. Christopher Mark Loney, Virginia P.E. NO. 029000. Detailed calculations were prepared as outlined in "Review of certification of Engineered Flood Openings," prepared by Dr. Georg Reichard, Associate Professor of Building Construction, Virginia Tech (available upon request from Crawl Space Door Systems, Inc. billy@crawlspacedoors.com)

Design Characteristics

Section 2.6.2.2 of ASCE/SEI 24-05 provides an equation to determine the required net area of engineered openings (A_o) for a given enclosed area (A_e). This equation is based on the hydraulic formula for the flow rate across sharp edged orifices. I have utilized this equation to calculate 1) the restricted flow rate through the main frame opening in case the louver is blown out during a flood event; 2) the flow rate through the individual openings between louver blades; and 3) the flow rate through projected openings between louver blades following hydraulic short-tube theory. The maximum total enclosed area (A_e) that can be serviced by a single vent has then been determined by utilizing the lowest flow rate of the three assessed scenarios for each vent and is listed in Table 1. These values are based on the following assumptions:

- In absence of reliable data, the rates of rise and fall have been assumed at a minimum rate of 5 feet/hour;
- The (maximum) difference between the exterior and interior floodwater levels shall not exceed 1 foot during base flood conditions;
- A factor of safety of 5 has been assumed, which is consistent with design practices related to protection of life and property;
- The net area of openings (A_o) as provided by the manufacturer.

*)	Model	11 X VV	Αď	Aو
		[in]	[in²]	[ft²]
	816CS	8 x 16	105	205
	1220CS	12 x 20	235	500
	1232CS	12 x 32	305	645
	1616CS	16 x 16	180	395
	1624CS	16 x 24	310	670
O	1632CS	16 x 32	405	835
	2032CS	20 x 32	630	1240
口	2424CS	24 x 24	570	1230
	2436CS	24 x 36	850	1765

HVW

Table 1 Maximum total <u>enclosed</u> <u>area</u> (A_e) that can be serviced by each individual model based on the given <u>net area</u> of engineered openings (A_o)

Installation Requirements and Limitations

This certification will be voided if the following installation requirements and limitations are not enforced:

- There shall be a minimum of two openings on different sides of each enclosed area subject to flooding;
- The bottom of all openings shall be no higher than one foot given net are above the higher of the interior or exterior grade that is immediately under each opening;
- No temporary (e.g. during cold weather) or permanent solid cover may be placed into or over the flood vent that would block the automatic entry or exit of floodwaters at any time;
- Where data or analyses indicate more rapid rates of rise and fall, the required number of openings shall be increased to account for those different conditions. The number or size of the openings may be decreased if data or analyses indicate rates of rise and fall are less than 5 feet per hour.

certifying Design Professional		
Name WILLIAM S. SWIDERSKI, P.E.	Title ENGINEER	
Company SWIDERSKI ASSSOCIATES		
Address 599 SHORE ROAD SOMERS POINT, NJ		
License PROFESSIONAL ENGINEER	License No. 24GE02048200	
Signature: Mm () ()	Date:	
dentification of the Building and Installed Flo	ood Vents (Ry Others)	
he flood vent models marked in Table 1*) are being installed	at the following building:	
		_

5pring 2012

Building Address