U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

IMPORTANT: Follow the instructions on pages 1–9.

OMB No. 1660-0008 Expiration Date: July 31, 2015

	SEC	CTION A -	PROPERTY IN	FORMAT	TION	OR INSURANCE	COMPANY USE
A1	Building Owner's Name IRONS CUSTOM HOMES				y	Policy Number:	
A2	Building Street Address (including Apt., Unit, Suite, an るち め、こしんれんのつい インドルリモ	id/or Bldg. N	lo.) or P.O. Route a	and Box N	lo.	Company NAIC Num	ber:
	City		State)	ZI	P Code 402	
A3.	Property Description (Lot and Block Numbers, Tax Pare LOT 11 BLOCK 204,01	cel Number,	Legal Description	, etc.)		00700	
A4. A5.	Building Use (e.g., Residential, Non-Residential, Additi Latitude/Longitude: Lat39,33550°		ry, etc.) <u>パ</u> モ - 74,49	51DEN		atum: 🗆 NAD 1	927 XNAD 1983
A6.	Attach at least 2 photographs of the building if the Ce.	rtificate is be	eing used to obta	in flood in	surance.	ZOIII. LINADI.	221 PX INVO 1903
	Building Diagram Number			AO For o	building with an atta		
no.	a) Square footage of crawlspace or enclosure(s).	92	2 sq ft		building with an atta quare footage of atta		sq ft
	b) No. of permanent flood openings in the crawlspace enclosure(s) within 1.0 foot above adjacent grade	or	2	b) Nu	umber of permanent thin 1.0 foot above a	flood openings in	
	c) Total net area of flood openings in A8.b	167	o sq in		tal net area of flood		sq ir
	d) Engineered flood openings? Skyes No	- 1740 P. Co 1840 P. Co		d) En	gineered flood open	ings? 🗌 Yes	□No
	SECTION B - FLOO	D INSURA	NCE RATE MA	AP (FIRM	M) INFORMATION		
B1.	NFIP Community Name & Community Number TY OF MARGATE CITY 3453	OU B	2. County Name	7/ 1.	ITIC,	В3.	State All
	Map/Panel Number B5. Suffix B6. FIRM Index		7. FIRM Panel Eff		B8. Flood Zone(s)	B9. Base Floor	d Elevation(s) (Zone
3.1.		_	Revised Date	_	4.0	AO, use ba	se flood depth)
	ROU OOO C 10/18/8 Indicate the source of the Base Flood Elevation (BFE) d	3	10 /18/8		A E	10	,0
	☐ FIS Profile ☐ FIRM ☐ Community Determined			ed in item	1 89;	-0	
B11.	Indicate elevation datum used for BFE in Item B9:	⊠NGVD 19	29 🗆 NAVD	1988	Other/Source: _		
	s the building located in a Coastal Barrier Resources S		S) area or Otherw	ise Prote	cted Area (OPA)? []Yes □No	
	Designation Date:/ CBR	s 🗆 c)PA		8	1. The state of th	
	SECTION C - BUILDIN	IG ELEVAT	ION INFORMA	TION (S	URVEY REQUIRE	D) 13-	172
	Building elevations are based on: Construction A new Elevation Certificate will be required when const	Drawings*	☐ Building e building is com	Under Co	nstruction*	Finished Constru	
C2. E	Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1 2.a–h below according to the building diagram specifie	–V30. V (wit	h BFE), AR, AR/A	AR/AE.	AR/A1-A30, AR/AH, meters.	AR/AO. Complete	e Items
E	enchmark Utilized: RM-I	51 OF 10 OF			V.GVD 19	29	
li D	ndicate elevation datum used for the elevations in item atum used for building elevations must be the same as	s a) through s that used t	h) below. 🔯 NG for the BFE.	SVD 1929			
) Top of bottom floor (including basement, crawlspace,		٧.	.]	Check the mea:	surement used.	
	Top of the next higher floor	or enclosure	1)	6	—	☐ meters \	
	Bottom of the lowest horizontal structural member (V	Zones only)	NIA		☐ feet	meters	\ /
d	Attached garage (top of slab)	9595,	NIA		feet	meters) (s
	Lowest elevation of machinery or equipment servicing (Describe type of equipment and location in Commen	ts)	s <u>11</u>	<u> </u>	feet	meters] lo s + 12
	Lowest adjacent (finished) grade next to building (LAG			.3		meters	202
	Highest adjacent (finished) grade next to building (HAC		/	.9_	⊠ feet	meters	
n)	Lowest adjacent grade at lowest elevation of deck or structural support	stairs, includ	dingl	6	⊠ feet	meters	
	SECTION D - SURVE	YOR, ENGI	NEER, OR ARC	CHITECT	CERTIFICATION		to the control of the
ormat	ification is to be signed and sealed by a land surveyor, on. I certify that the information on this Certificate repre	engineer, or	architect authori	ized by lav	w to certify elevation		-11
	and that any false statement may be punishable by fine here if comments are provided on back of form.					G5 33	541
	1 17 11	licensed lan	e and longitude ind d surveyor? 5	The state of the s	A provided by a ☐ No		a.
ertifier's	Name	The second se		cense Nun		-1 1	PLACE
1-10	WARD A. TRANSUE			55 33			SEAL
ile Rol	ESSIONAL LAND SURVEYOR	Company Nati		SCHEIF	EGG. CE, LLC		HERE
ldress		City	Sta	ate	ZIP Códe	ا ا	124/2013
25 gnature	CANTILLON BOULEVARD	Date 1	ANDING Tel	ephone	08330	$-\parallel$.l
	NIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	17/17/1	12013 /1	-0011	25 -11/00	1.1	

ELEVATION CERTIFICATE, page 2

from Section A.	
.) or P.O. Route and Box No.	FOR INSURANCE COMPANY USE Policy Number:
ZIP Code	Company NAIC Number:
00100	TION (CONTINUED)
	THE STATE OF THE PROPERTY OF T
31 ACC 20012 3 13 16 113 VE	NI) KHIEV NI 6 33 30, W. EAC
Dota /	***************************************
12/24/2	013
SURVEY NOT REQUIRED) FOR Z	ONE AO AND ZONE A (WITHOUT BFE)
tificate is intended to support a LOMA	or LOMR-F request, complete Sections A, B, and C.
1.50	
	station to above of below the highest adjacent
	meters above or below the HAG.
	meters above or below the LAG.
	meters above or below the HAG.
	meters above or below the HAG.
하는데 그렇게 하는데 이번 사람들은 함께 보고 있다면 하는데 하는데 하는데 하는데 하는데 하는데 되었다. 그 사람이 없는데 하는데 하는데 하는데 하는데 하는데 하는데 하는데 하는데 하는데 하	meters above or below the HAG.
st certify this information in Section G.	e with the community's noodplain management
(OR OWNER'S REPRESENTATIV	E) CERTIFICATION 13-172
tes Sections A. B. and E for Zone A (wi	thout a FEMA-issued or community-issued BFE) or
correct to the best of my knowledge.	
City	State ZIP Code
Date	Telephone
	☐ Check here if attachments.
JUNITY INFORMATION (OPTION	AL)
community's floodplain management o	rdinance can complete Sections A, B, C (or E), and
below. Check the measurement used in	n Items G8-G10. In Puerto Rico only, enter meters.
itation that has been signed and seal	ed by a licensed surveyor, engineer, or architect
nmunity floodplain management purpo	
d G6. Date Certif	icate Of Compliance/Occupancy Issued
Substantial Improvement	
	☐ meters Datum
and the state of t	
Title	
Talanhar Construct	
Telephone 6	
822-1	974
Date 822 -/	974
822-1	974
822-1	974
822-1	974
E a contraction of the contracti	Date Date 12/24/2

Certification of Engineered Flood Openings

In accordance with NFIP, FEMA TB 1-08, and ASCE/SEI 24-05

I hereby certify that the Crawl Space Door Systems flood vents 816CS, 1220CS, 1232CS, 1616CS, 1624CS, 1632CS, 2032CS, 2424CS, and 2436CS are designed in accordance with the requirements of the NFIP "Flood insurance Manual" (2011) to provide automatic equalization of hydrostatic flood forces by allowing for the entry and exit of floodwaters, when properly installed and sized as set forth below. This certification follows the design requirements and specifications established in FEMA Technical Bulletin 1-08, "Openings in Foundation Walls and Walls of Enclosures Below Elevated Buildings in Special Flood Hazard Areas", and the ASCE Standard for "Flood Resistant Design and Construction" (ASCE/SEI 24-05).

Design Characteristics

Section 2.6.2.2 of ASCE 24 provides an equation to determine the required <u>net area</u> of engineered openings (A_o) for a given <u>enclosed area</u> (A_e) . This equation is based on the hydraulic formula for the flow rate across sharp edged orifices. I have utilized this equation to calculate 1) the respected flow rate through the individual openings between louvers; 2) the flow rate through the main frame opening in case the louver is blown out during a flood event; and 3) the flow rate of water flowing through louver blades following hydraulic short tube theory. The ultimate maximum total enclosed area (A_e) that can be serviced by a single vent has then been determined by utilizing the lowest flow rate of the three assessed scenarios for each vent and is listed in Table 1.

These values are based on the following assumptions:

- In absence of reliable data, the rates of rise and fall have been assumed with 5 feet/hour;
- The (maximum) difference between the exterior and interior floodwater levels has been assumed with 1 foot during base flood conditions;
- A factor of safety of 5 has been assumed, which is consistent with design practices related to protection of life and property;
- The net area of openings (A_o) as provided by the manufacturer.

Installation Requirements and Limitations

This certification will be voided if the following installation requirements and limitations are not enforced:

- There shall be a minimum of two openings on different sides of each enclosed area;
- The bottom of each required opening shall be no more than 1ft above the adjacent ground level;

*)	Model	H x W [in]	A _o [in ²]	A _e [ft ²]
	816CS	8 x 16	105	205
	1220CS	12 x 20	235	500
	1232CS	12 x 32	305	645
	1616CS	16 x 16	180	395
	1624CS	16 x 24	310	670
	1632CS	16 x 32	405	835
	2032CS	20 x 32	630	1240
	2424CS	24 x 24	570	1230
	2436CS	24 x 36	850	1765

Table 1 Maximal total <u>enclosed area</u> (A_e) that can be served by each individual model based on the given <u>net area</u> of engineered openings (A_o)

- No temporary (e.g. during cold weather) or permanent solid cover may be placed into or over the flood vent that would block the automatic entry or exit of floodwaters at any time;
- Where analysis indicates rates of rise and fall greater than 5 ft/hr, the total enclosed area as given in Table 1 shall be reduced accordingly to account for the higher rates of rise and fall.

Identification of the Building and Installed Flood Vents

The flood vent models marked in Table 1*) are being installed at the following building:

Building Address

Certifying Design Professional

Name	WILLIAM S. SWIDERSKI, P.E.	
Title	ENGINEER	
Address	599 SHORE ROAD, SOMERS P	OINT, NJ 08244
Type of License	PROFESSIONAL ENGINEER	INV and WYD I
License #	20482	Signature
Issuing State	NFW IERSFY	7/24/(2

