U.S. DEPARTMENT OF HOMELAND SECURITY FEDERAL EMERGENCY MANAGEMENT AGENCY National Flood Insurance Program

ELEVATION CERTIFICATE

Important: Read the instructions on pages 1-9.

OMB No. 1660-0008

Expiration Date: July 31, 2015

	SECTION A - PROPERTY INFO	DRMATION FOR	insurange companyuse 🧀		
A1. Building Owner's Name Shore Point Homes			y/Numlo⊝is		
A2. Building Street Address (including Apt., Unit, Suite 212 N. Belmont Ave.	and/or Bldg. No.) or P.O. Route and B	ox No. Com	oany NAIC Number:		
City CITY OF MARGATE CITY	State NJ ZIP Co	de 08402			
A3. Property Description (Lot and Block Numbers, Tax BLOCK 502.03 LOT 75	Parcel Number, Legal Description, etc	.)			
A4. Building Use (e.g., Residential, Non-Residential, Addition, Accessory, etc.) RESIDENTIAL A5. Latitude/Longitude: Lat. N 39.3366 Long. W 074.4979 Horizontal Datum: NAD 1927 NAD 1983 A6. Attach at least 2 photographs of the building if the Certificate is being used to obtain flood insurance. A7. Building Diagram Number 8 A8. For a building with a crawlspace or enclosure(s): a) Square footage of crawlspace or enclosure(s) b) Number of permanent flood openings in the crawlspace or enclosure(s) within 1.0 foot above adjacent grade 5 c) Total net area of flood openings? Nes No A9. For a building with an attached garage: a) Square footage of attached garage N/A sq ft b) Number of permanent flood openings in the attached garage within 1.0 foot above adjacent grade N/A c) Total net area of flood openings? Nes No d) Engineered flood openings? Yes No					
SECTION B - I	FLOOD INSURANCE RATE MAP	(FIRM) INFORMATION			
B1. NFIP Community Name & Community Number CITY OF MARGATE 345304	B2. County Name ATLANTIC COUNTY	B3. S NJ	State		
	I Index Date B7. FIRM Panel Effective/Revised Date 10/18/1983		9. Base Flood Elevation(s) (Zone AO; use base flood depth) 10**		
Indicate the source of the Base Flood Elevation (BFE) data or base flood depth entered in Item B9. FIS Profile FIRM Community Determined Other/Source: S11. Indicate elevation datum used for BFE in Item B9: NGVD 1929 NAVD 1988 Other/Source: S12. Is the building located in a Coastal Barrier Resources System (CBRS) area or Otherwise Protected Area (OPA)? Yes No Designation Date: CBRS OPA					
SECTION C - BUI	LDING ELEVATION INFORMATION	ON (SURVEY REQUIRED)			
C1. Building elevations are based on: Construction Drawings* Building Under Construction* Finished Construction *A new Elevation Certificate will be required when construction of the building is complete. C2. Elevations – Zones A1–A30, AE, AH, A (with BFE), VE, V1–V30, V (with BFE), AR, AR/A, AR/AE, AR/A1–A30, AR/AH, AR/AO. Complete Items C2.a–h below according to the building diagram specified in Item A7. In Puerto Rico only, enter meters. Benchmark Utilized: private Vertical Datum: NGVD 1929 Indicate elevation datum used for the elevations in items a) through h) below. NGVD 1929 NAVD 1988 Other/Source: Datum used for building elevations must be the same as that used for the BFE.					
a) Top of bottom floor (including basement, crawlsp	ace or enclosure floor)		measurement used. eet		
b) Top of the next higher floor c) Bottom of the lowest horizontal structural membe d) Attached garage (top of slab) e) Lowest elevation of machinery or equipment serv (Describe type of equipment and location in Com	r (V Zones only)	8.6 ⋈ fe 12.3 ⋈ fe N/A. ⋈ fe 12.6**** ⋈ fe	pet meters pet meters pet meters pet meters		
 f) Lowest adjacent (finished) grade next to building g) Highest adjacent (finished) grade next to building h) Lowest adjacent grade at lowest elevation of dec 	(LAG) (HAG)	8.4	eet meters		
SECTION D - SURVEYOR, ENGINEER, OR ARCHITECT CERTIFICATION					
This certification is to be signed and sealed by a land s information. <i>I certify that the information on this Certific I understand that any false statement may be punishab</i> ☑ Check here if comments are provided on back of f ☑ Check here if attachments. Certifier's Name Paul M. Koelling, PLS, CFM	ate represents my best efforts to interp le by fine or imprisonment under 18 U. orm. Were latitude and longitude licensed land surveyor?	ret the data available. S. Code, Section 1001.	PLACE SEAL HERE		
Certifier's Name Faul W. Roelling, FLS, Of W					
Title Licensed Land Surveyor Company		, LLC	-		
Title Licensed Land Surveyor Company Address 2161 Shore Boad City Linw	Name Paul H. Koelling & Associates	, LLC ZIP Code 08221	-		

LLL VALION OLIVIII IOALE, Pa	ye 2			
IMPORTANT: In these spaces, copy the corresponding information from Section A.			FORIN	ISURANCE COMPANY LISE
Building Street Address (including Apt., Unit, Suite, and/or Bldg. No.) or P.O. Route and Box No. 212 N. Belomont Ave.		and Box No.	Policy Number:	
City MARGATE	State NJ	ZIP Code 08402	Compa	ny NAIC Number:
SECTION	D – SURVEYOR, ENGINEER, OR ARC	CHITECT CERTIFICATION	ON (CONTINI	UED)
Copy both sides of this Elevation Certif	icate for (1) community official, (2) insurance	agent/company, and (3) bu	uilding owner.	9
Comments *A8b.) Foundation Openings **B8 & B9.) FEMA Pre-FIRM Zone AE ***C2a.) crawlspace	Base Flood Elevation 8 ft. (NAVD88) con	verted = 9.3 ft. (NGVD29)		
Signature	D	ate 5/4/15		
	VATION INFORMATION (SURVEY NO	T REQUIRED) FOR ZO	NE AO AND 2	ZONE A (WITHOUT BFE)
 and C. For Items E1–E4, use natural general series (HAG) and the lowest adjacent (HAG) and the lowest adjacent (HAG) and the lowest (HAG) and the lowe	basement, crawlspace, or enclosure) isbasement, crawlspace, or enclosure) is permanent flood openings provided in Sectio of the building is	sed. In Puerto Rico only, eles to show whether the elevant of the set of the	nter meters. vation is above neters	or below the highest adjacent e or below the HAG. e or below the LAG. structions), the next higher floor i.
	F – PROPERTY OWNER (OR OWNER		CERTIFICA	TION
	zed representative who completes Sections Annents in Sections A, B, and E are correct to the Representative's Name		out a FEMA-iss	sued or community-issued BFE)
Address	City		State	ZIP Code
Signature	Date		Telephone	
Comments .				☐ Check here if attachments
	SECTION G - COMMUNITY INF			
of this Elevation Certificate. Complete the G1. The information in Section C v is authorized by law to certify or the complete the co	or ordinance to administer the community's fl applicable item(s) and sign below. Check the was taken from other documentation that has elevation information. (Indicate the source a d Section E for a building located in Zone A	measurement used in Items been signed and sealed by nd date of the elevation dat	s G8–G10. In Pi y a licensed sur a in the Commo	uerto Rico only, enter meters. veyor, engineer, or architect who ents area below.)
G3. The following information (Iten	ns G4–G10) is provided for community flood	plain management purpose	S.	
G4. Permit Number	G5. Date Permit Issued	G6. Date Certificate	e Of Complianc	e/Occupancy Issued
G7. This permit has been issued for: G8. Elevation of as-built lowest floor (in G9. BFE or (in Zone AO) depth of flood G10. Community's design flood elevation Local Official's Name Community Name	cluding basement) of the building:ling at the building site:	al Improvement feet met feet met feet met feet met Title Feet	ers Datu	m m m
Signature	Margall	Date 7/13/12	22-1911	1
Comments				
·				Check here if attachments

Building Photographs

	Continuation P	•	For Insurance Company Use:
Building Street Address (incl 212 N. Belmont Ave.	Policy Number		
City Margate	State NJ	ZIP Code 08402	Company NAIC Number

If submitting more photographs than will fit on the preceding page, affix the additional photographs below. Identify all photographs with: date taken; "Front View" and "Rear View"; and, if required, "Right Side View" and "Left Side View."





Front View – Date of Photograph: (See Photo Stamp)

Rear View – Date of Photograph: (See Photo Stamp)





Right Side View – Date of Photograph: (See Photo Stamp)

Vent View – Date of Photograph: (See Photo Stamp)



ICC-ES Evaluation Report

ESR-2074

Reissued February 1, 2009

This report is subject to re-examination in two years.

www.lcc-es.org | (800) 423-6567 | (562) 699-0543

A Subsidiary of the International Code Council®

DIVISION: 10—SPECIALTIES Section: 10230—Vents

REPORT HOLDER:

SMART VENT[®], INC. 450 ANDBRO DRIVE, SUITE 2B PITMAN, NEW JERSEY 08071 (856) 307-1468 www.smartvent.com eval@smartvent.com

EVALUATION SUBJECT:

SMART VENT® AUTOMATIC FOUNDATION FLOOD VENTS:
FLOODVENT™ MODEL #1540-520; FLOODVENT™
STACKING MODEL #1540-521; SMARTVENT™ MODEL
#1540-510; SMARTVENT™ STACKING MODEL #1540-511;
WOOD WALL FLOOD MODEL #1540-570; WOOD WALL
FLOOD OVERHEAD DOOR MODEL #1540-574;
FLOODVENT™ OVERHEAD DOOR MODEL #1540-524;
SMARTVENT™ OVERHEAD DOOR MODEL #1540-614

1.0 . EVALUATION SCOPE

Compliance with the following codes:

- 2006 International Building Code[®] (IBC)
- 2006 International Residential Code® (IRC)

Properties evaluated:

- Physical operation
- Water flow

2.0 USES

The Smart Vent[®] units are automatic foundation flood vents (AFFVs) employed to equalize hydrostatic pressure on nonfire-resistance-rated foundation walls, rolling-type overhead doors and building walls subject to rising or falling flood waters. Certain models also allow natural ventilation in accordance with Section 1203 of the IBC or Section 408.1 of the IRC.

3.0 DESCRIPTION

3.1 General:

When subjected to pressure from rising water, the Smart Vent[®] AFFVs disengage, then pivot open to allow flow in either direction to equalize water level and hydrostatic pressure from one side of the foundation to the other. The AFFV pivoting door is normally held in the closed position by a buoyant release device. When subjected to rising water, the buoyant release device causes the unit to

unlatch, allowing the plate to rotate out of the way and allow flow. The water level stabilizes, equalizing the lateral forces. Each unit is fabricated from stainless steel, and each opening provides 76 square inches (49 032 mm²) of net free area for flood mitigation in the open position. The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units each contain two vertically arranged openings per unit, providing 152 square inches (98 064 mm²) of net free area for flood mitigation in the open position.

3.2 Engineered Opening:

The AFFVs comply with the design principle noted in Section 2.6.2.2 of ASCE/SEI 24 for a maximum rate of rise and fall of 5.0 feet per hour (0.423 mm/s). In order to comply with the engineered opening requirement of ASCE/SEI 24, Smart Vent AFFVs must be installed in accordance with Section 4.0.

3.3 Model Sizes:

The FloodVENT™ Model #1540-520, SmartVENT™ Model #1540-510, FloodVENT™ Overhead Door Model #1540-524, and SmartVENT™ Overhead Door Model #1540-514 units measure 15³/₄ inches wide by 7³/₄ inches high (400 by 196.9 mm). The Wood Wall Flood Model #1540-570 and Wood Wall Flood Overhead Door Model #1540-574 units measure 14 inches wide by 8³/₄ inches high (355.6 by 222.25 mm). The SmartVENT™ Stacking Model #1540-511 and FloodVENT™ Stacking Model #1540-521 units measure 16 inches wide by 16 inches high (406.4 by 406.4 mm).

3.4 Ventilation:

The SmartVENT® Model #1540-510 and SmartVENT® Overhead Door Model #1540-514 both have screen covers with ¹/₄-inch-by-¹/₄-inch (6.35 by 6.35 mm) openings, yielding 51 square inches (32 903 mm²) of net free area to supply natural ventilation. The SmartVENT™ Stacking Model #1540-511 consists of two Model #1540-510 units in one assembly, and provides 102 square inches (65 806 mm²) of net free area to supply natural ventilation. Other AFFVs recognized in this report do not offer natural ventilation.

4.0 INSTALLATION

SmartVENT® and FloodVENT™ are designed to be installed into wells or overhead doors of existing or new construction from the exterior side. Installation of the vents must be in accordance with the manufacturer's instructions, the applicable code and this report. The mounting straps allow mounting in wood, masonry and concrete walls up to 12 inches (305 mm) thick. In order to

Page 1 of 2